

CHIMNEY RX CREOSOTE REMOVER

PRODUCT DATA

Chimney RX Creosote Remover

MANUFACTURER: SaverSystems

Richmond, IN 47374

800-860-6327

Fax 765-935-4999

www.chimneyrx.com

DESCRIPTION

Chimney RX Creosote Remover is a non-toxic and environmentally safe liquid manganese catalyst that attacks and destroys dangerous creosote and soot. When sprayed daily into the firebox during low fire conditions, Chimney RX Creosote Remover helps convert creosote and soot to a harmless ash or char that can be easily removed.

USES

Chimney RX Creosote Remover is an effective maintenance product used to help control dangerous creosote and soot deposits in all wood and coal burning appliances. A simple daily application during the heating season helps convert glazed creosote to a harmless ash or char that can be easily removed. Chimney RX Creosote Remover also reduces ash and clogging in pellet stoves.

BENEFITS

- Attacks dangerous creosote & soot
- Helps prevent chimney fires
- Chimneys clean easier and more completely
- Reduces odors and pollution
- Reduces corrosion in metal & masonry chimneys
- Safe for use with catalytic combustors
- Non-toxic & easy to use

DIRECTIONS FOR USE

For best results use daily during the heating season. Have severe conditions inspected and corrected by a qualified chimney sweep before using Chimney RX Creosote Remover.

Wood Burning Appliances:

First Time Use: With a small fire burning, spray about 60 squirts (about 4oz.) on the interior walls of the firebox, on the wood, and in the general direction of the flue.

Daily Use: Spray on the inside of the firebox, on the wood, and toward the flue, 6-12 squirts total. In severe cases, use up to 60 squirts a day in above manner for the first 7 days, then 6-12 squirts daily. There is no harm in liberal use of the product.

After Treatment: Continue with a small, brisk fire for at least 45 minutes. Chimney RX Creosote Remover becomes active at temperatures of 300°F. & above (surface stove pipe temperatures). Use a small charge of wood to avoid overheating during early stages of creosote control. Remove dried creosote & soot from stovepipe and elbows as necessary to avoid obstructions.

Coal: Similar procedure except do not spray Chimney RX Creosote Remover directly onto hot coals.

Pellet stoves: Apply daily to hopper & fire chamber to reduce ash & clogging.

Stoves with Catalytic Combustors: Put combustor in bypass mode before treatment and for about 1 hour afterwards. Never spray AChimney RX Creosote Remover on an operating or hot catalytic combustor.

MAINTENANCE

Have chimney cleaned and inspected at least once a year by a qualified chimney sweep.

Cleaning Spills: Remove stains on hard surfaces by adding a few drops of white vinegar to hydrogen peroxide. Apply to stains, and then blot up. Rinse textiles with water before product dries.

CAUTIONS

Keep out of reach of children. Eye Irritant. Avoid contact with eyes, mucous membranes, and prolonged contact with skin.

First Aid: In case of eye, contact flush with plenty of water for at least fifteen minutes and get proper medical attention. In case of skin contact, wash as soon as possible with soap and water. In case of ingestion, drink plenty of water, and contact a physician immediately.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Chimney RX Creosote Remover is packaged in 32 oz. recyclable spray bottles.

TRANSPORT AND STORAGE

Chimney RX Creosote Remover is not considered a hazardous material or substance under U.S. Department of Transportation (DOT) regulations. Store in a cool dry place inaccessible to children and animals. Keep from freezing.